



HARRISON LIMITED

Technical Information

Stitching Wire

Stitching Wire is now referred to as 'Alloy Coated' and not as Galvanised.

Wire is boxed in 5's and spooled on 'C22' spools, of which a spool deposit is charged.

If Wire is to be despatched in smallish quantities the cheapest method is to re-box and despatch by parcel post in quantities of 10's.

A new type of spool referred to as a 'GL' is being introduced which will be boxed in 6's, a spool deposit is also charged.

N.B.

We will despatch wire by the cheapest possible route either by carrier or post. This may require supplying slightly more or less than ordered.

Available from stock:			
ISWG Wire Gauge	Size in mm	Size in inches	
ROUND WIRES			
26	.46	.018"	
25	.50	.020"	Recommended for all Wire Stitching Heads
24 ^{1/2} "	.53	.021"	
24	.56	.022"	Recommended for Boston No7 up to 3/16"
23	.60	.024"	
NARROW FLAT WIRES			
21 X 25	.80 X .50	.032" X .020"	Suitable for Heads converted to flat wire
20 x 24	.90 x .56	.036" x .022"	Recommended for Boston No7 up to 3/4"
19 x 21	1.00 x .80	.040" x .032"	
NARROW HARD FLAT WITES			
20 X 24	.90 X .56	.036" X .022"	Recommended for Boston No7 over 3/4"
19 x 21	1.00 x .80	.040" x .032"	
18 x 19	1.18 x 1.00	.047" x .040"	